

SH-400 网口接口



主要应用/Applications

SH-400采用先进的成像技术,具有良好的条码扫描和数字图像采集功能,实现了稳定性能和快速识读,并增强了低质量条码的识读性能。从普通一维条码到移动设备屏幕上的二维条码都能读取。

SH-400 adopts advanced imaging technology and has good bar code scanning and digital image acquisition functions, achieving stable performance and fast reading, and enhancing the reading performance of low quality bar codes. They range from a 1D bar code to a 2D bar code on the screen of a mobile device.

特点/Feature

- ★ **解码技术:**对各种一维、二维码的解码,实现快速精准扫描。
- ★ **高性能扫描技术:**支持市面通用的条码,支持破损、变形条码扫描,同时支持电脑、手机、平板等屏幕二维码扫描。
- ★ **广泛应用设备:**超小体积,广泛应用移动手持终端、POS支付、设备柜、智能机器人等物联网产业链。
- ★ **Decoding technology:**To all kinds of 1D, 2D code decoding, fast and accurate scanning.
- ★ **High-performance scanning technology:**Supports the scanning of damaged and deformed bar codes, as well as the scanning of 2D codes on the screens of computers, mobile phones, and tablets.
- ★ **Widely used equipment:**Ultra-small size, widely used in mobile handheld terminals, POS payment, equipment cabinets, intelligent robots and other iot industry chain.

技术参数/Technical Specifications

物理参数/Physical Parameters

外形尺寸 Overall dimensions	49mm*43mm*22mm	产品重量 Product weight	60g
包装尺寸 Packing size	190mm*110mm*80mm	包装重量 Packing weight	200g
外壳材质 Shell material	ABS	LED指示 LED indicator	红色、绿色
背景光源 Background light source	白色LED	定位光源 Positioning the light source	红色LED

性能参数/Performance Parameter

工作电压 Working voltage	5V或(or)10V-48V
直流电源 Dc power supply	Class2;5.2VDC@1A
工作功率 Working power	0.6W 150mA/3.7V
待机功率 Standby power	0.07W 20mA/3.7V
支持条码类型 Supported bar code types	标准一维, 二维条码 (PDF417,QR,Data Matrix)
扫描类型 Scanning type	影像式
系统接口 System interface	网口接口(支持POE)
触发控制 Trigger control	IO输入触发控制、输出脉冲3.3V/0.5秒指示、PLC通断高低电平检测
通信距离 Communication distance	0-200米

环境参数/Environmental Parameters

操作温度 Operating temperature	-10℃-50℃
储存温度 Storage temperature	-40℃-60℃
操作湿度 Operating humidity	5%-95%相对湿度, 非凝结状态
静电防护 Electrostatic protection	±15kVDC空气放电, ±8kVDC直接/间接放电
跌落试验 Drop test	100次/1M
受光强度 By the light intensity	0-100.000LUX
运动容差 Exercise tolerance	100毫米/秒13milUPC
IP等级 IP rating	参照IP54设计标准
防尘性 Dustproof sex	密封以抵挡空气尘粒侵入
综合认证 Comprehensive certification	ROHS、FCC、CE

产品性能/Product Performance

条码密度/Bar code density

- ★ 4mil Code39
- ★ 6.67mil PDF417
- ★ 10mil Data Matrix
- ★ 13mil EAN-13
- ★ 20mil QR Code

扫描景深/Scan Depth

- 40-90mm
- 30-130mm
- 50-90mm
- 50-200mm
- 25-240mm

此数据可能因条码质量和环境因素而不同。